



# Your COMPLETE TRENCH source!



Enviro-Flo® II  
9930 Series

## Polypropylene Trench Drain System

- Lightweight, 1m length joined by mechanical locking joint.
- Channels joined by mechanical locking joint
- 20 Pre-Sloped Channels beginning at a depth of (minimum depth should be stated)
- 20 Neutral Channels beginning at a depth of 4.38" - 9.12"
- Quick-Lok grate lockdowns
- 4" No-Hub Bottom Outlets on every channel
- Integral Rebar Support Clips for ease of elevation set



2700 Series

## Cast Iron Trench Drain System

- Heavy duty modular drain for loading or parking areas.
- Available with flange and clamping collar.
- Cast Iron Trench 1' length



9812 Series

## Fiberglass Trench Drain System

- High strength, light weight, and corrosion-resistant.
- 12 sloped channels, 8 neutral channels are each nine feet in length and channel depth varies from 6.88 to 20.38 inches.
- 9' length
- Channel Depth Varies 6.88" to 20.38"



9895 Series

## Polymer Concrete Trench Drain System

- Varying widths and depths to meet application needs—1m in length.
- Anchor ribs offer security against upward movement or shifting after installation.
- Widths vary from 3.2" to 14" -Lengths from 1/2 meter (19.68") to 1 meter (39.36")
- Integral rails Galvanized, Stainless Steel, Ductile Iron
- Anchor ribs for mechanical lock into the surrounding concrete



9660 Series

## Stainless Steel Modular Trench Drain System

- All drains constructed from 16 gage, type 304 Stainless Steel, type 316 Stainless Steel is optional.
- Sanitary Food Service, Chemical Resistance, Aesthetics
- Pre-engineered with a .6% built in slope
- 1 meter lengths (39.36") Flanged bolt together ends with gaskets



9666 Series

## Linear Shower Drain System

- 2" wide barrier free threshold drain for shower stall.
- Vandal-proof ADA compliant perforated or slotted grates.
- Optional flange or clamping collar w/weep holes
- Optional 2" NPT or 2"x 3" bottom outlet connection with model 215/216 floor drain
- Standard lengths 24", 32" 36", 42" 48" 60"
- Custom lengths available

Grate offering ranges from ADA pedestrian rated to 202,320 lb wheel loads



**JAY R. SMITH MFG. CO.®**

MEMBER OF MORRIS GROUP INTERNATIONAL

P.O. Box 3237 • Montgomery, AL 36109  
TEL: 334.277.8520

[www.jrsmith.com](http://www.jrsmith.com)



MORRIS GROUP  
INTERNATIONAL  
[www.morrisgroup.co](http://www.morrisgroup.co)

SPM3008-1505