

C	<div style="display: flex; justify-content: space-between; align-items: center;"> <div style="width: 30%;"> <p>SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com</p> </div> <div style="width: 30%; text-align: center;"> <p>MEMBER OF:</p> </div> <div style="width: 30%; text-align: center;"> <p>MEMBER OF:</p> </div> </div>					LOCATION															
	SPECIAL PURPOSE ROOF DRAIN																				
	16" (406) DIAMETER - LOW PROFILE FLAT GRATE																				
	<div style="position: absolute; top: 20px; right: 20px; text-align: right;"> Free Area 32.6 Sq. In. (210 Sq. Cm.) </div>																				
<div style="display: flex; justify-content: space-between;"> <div style="width: 30%;"> <p>Labels:</p> <ul style="list-style-type: none"> Combined Flashing Clamp and Gravel Stop Sump Receiver (When Specified) Underdeck Clamp (When Specified) </div> <div style="width: 40%;"> <p>Dimensions:</p> <ul style="list-style-type: none"> 15 1/4(390) Dia. 12(305) Dia. 11 1/2(290) Dia. 11(280) Dia. Δ4 3/4 (120) A B </div> <div style="width: 30%;"> <p>Labels:</p> <ul style="list-style-type: none"> Cast Iron Slotted Grate Water Proofing Membrane Concrete Slab </div> </div>																					
<div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> <p>Δ This Dimension to Internal Stop of Speedi-Set® Gasket</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>REGULARLY FURNISHED:</p> <p>Duco Cast Iron Body, Combined Flashing Clamp and Gravel Stop with ADA Slotted Cast Iron Grate.</p> </div> <div style="width: 45%;"> <p>VARIATIONS:</p> <ul style="list-style-type: none"> <input type="checkbox"/> L Speedi-Set® Service Weight Outlet Conn. (02, 03, & 04 Sizes Only) <input type="checkbox"/> LXH Speedi-Set® Extra Heavy Duty Outlet Conn. (02, 03, & 04 Sizes Only) <input type="checkbox"/> Sump Receiver -R <input type="checkbox"/> Underdeck Clamp -C <input type="checkbox"/> Vandal Proof Dome -U <input type="checkbox"/> T Threaded Outlet </div> </div> </div> <div style="width: 35%;"> <p>OPTIONAL MATERIALS:</p> <p><input type="checkbox"/> Galvanized Cast Iron Body and Collar -G</p> </div> </div>																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">A SIZE</td> <td style="width: 10%;">02 (50)</td> <td style="width: 10%;">03 (75)</td> <td style="width: 10%;">04 (100)</td> <td style="width: 10%;">05 (125)</td> <td style="width: 10%;">06 (150)</td> </tr> <tr> <td>B</td> <td colspan="5">5 (127) for Caulk, No Hub and Speedi-Set® 3 3/4" (120) for Threaded</td> </tr> </table>										A SIZE	02 (50)	03 (75)	04 (100)	05 (125)	06 (150)	B	5 (127) for Caulk, No Hub and Speedi-Set® 3 3/4" (120) for Threaded				
A SIZE	02 (50)	03 (75)	04 (100)	05 (125)	06 (150)																
B	5 (127) for Caulk, No Hub and Speedi-Set® 3 3/4" (120) for Threaded																				
<div style="display: flex; justify-content: space-between;"> <div style="width: 30%;"> <p>Fig. 1010C (-GRT) CAULK OUTLET</p> <p>Fig. 1010Y (-GRT) NO-HUB OUTLET</p> </div> </div>																					
<div style="display: flex; justify-content: space-between;"> <div style="width: 30%;"> <p>FIGURE NUMBER</p> <p style="font-size: 24px; font-weight: bold;">1010 (-GRT)</p> </div> <div style="width: 30%;"> <p>REV.</p> <p>DATE</p> </div> <div style="width: 30%;"> <p>DESCRIPTION</p> </div> <div style="width: 10%;"> <p>BY</p> </div> <div style="width: 10%;"> <p>CKD. BY</p> </div> <div style="width: 10%;"> <p>WEIGHT POUNDS</p> </div> <div style="width: 10%;"> <p>VOLUME CUBIC FEET</p> </div> <div style="width: 30%;"> <p>FIGURE NUMBER</p> <p style="font-size: 24px; font-weight: bold;">1010 (-GRT)</p> </div> </div>																					