

STORAGE TANK FLOATING FILTERS AND HOSES

FUNCTION: The floating filter is used to extract and filter rainwater out of the storage tank, cistern, pond or well.



Fig. RH9532C
 Coarse Filter Housing with 1200 micron Mesh and 1 1/4" (32) Connection (WISY SZ9928)



Fig. RH9532F
 Fine Filter Housing with 300 micron Mesh and 1 1/4" (32) Connection (WISY SZ9936)



Fig. RH9532C-2
 Coarse Filter Housing with 1200 micron Mesh and 2" (51) Connection (WISY SZ9991)



Fig. RH9532F-2
 Fine Filter Housing with 300 micron Mesh and 2" (51)" Connection (WISY SZ9931)



A product of WISY AG in cooperation with RMS.

REGULARLY FURNISHED:
 Stainless Steel Floating Filter, Polyethylene Float Ball, 7' Long Connection Hose Suitable for Suction or Submersible Pumps.

NOTE: Longer hoses are available through your local representative.

NOTE: Dimensions shown in parentheses are in millimeters.

DRAWING NUMBER
 SRH9532

SIZE
 A

SCALE:
 NONE

DATE:
 09/21/07

APPROVED BY:
 TWK

CHECKED BY:
 TWK

DRAWN BY:
 JJ

RH9532

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

FIGURE NUMBER

A	02/02/09	Revised Text	JJ	TWK
REV.	DATE	DESCRIPTION	BY	CKD. BY

WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER RH9532
---------------	-------------------	--------------------------------